

Product Technical Statement
Legni del Doge

Teak Africa wood

1. Unique identification code for product type n.: **IT-LDDTK-rev.03/21 - Legni del Doge, multi-layer wood flooring.**
2. Type, batch or serial number, or any other element with which to identify a construction product, pursuant to article 11, paragraph 4: **Two-layer wood flooring with solid wood top layer, nominal thickness 3mm, and second layer in phenolic birch plywood.**
3. Intended use or uses of construction product, conforming to the relative harmonised technical specifications, as established by the manufacturer: **Wood flooring for indoor use, in compliance with harmonized UNI EN 14342:2013 Standards.**
4. Manufacturer's name, registered trade name or mark and address, pursuant to article 11, paragraph 5: **ITLAS S.r.l., Via del Lavoro 35, zona industrial, 31016 Cordignano (TV).**
5. If applicable, name and address of the agent whose mandate includes the tasks mentioned in art. 12, paragraph 2: **Not applicable.**
6. System or systems used to assess and verify the construction product's performance, as per appendix V: **System 4 (product characteristics extrapolated from the product info sheet and production control). System 3 with regard to reaction to fire and formaldehyde emissions.**
7. In the case of a declaration of performance concerning a construction product included in the application of harmonised standards: **Notified test laboratory (No. 0006) CSI S.p.a. – 20030 Senago (MI) has carried out the tests regarding reaction to fire, and notified test laboratory (No. 0027) Catas S.p.a. – 33048 S. Giovanni al Natisone (UD) has performed the tests regarding formaldehyde emissions.**
8. In the case of a declaration of performance concerning a construction product for which a European technical assessment has been issued: **Not applicable.**
9. Declared performance:

Essential characteristics	Performance	Harmonised technical specifications
Reaction to fire	Cfl-s1 / Dfl-s1 *	EN 14342:2013 + A1:2008
Formaldehyde emissions	E1	
Thermal conductivity	NDP	
Slipperiness	NDP	
Breaking point	NDP	
Biological durability	1 ÷ 2	

* Dfl-s1 for all those finishes whose code begins with letters E-P-R (e.g.: TKLLD3ML--P001QND003)

10. Performance of the product mentioned in points 1 and 2 hereof complies with the performance declared in point 9. This Product Technical Statement is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer
Dei Tos Patrizio - Legal representative