

DECLARATION OF PERFORMANCE n. TKLDD3Dfl-s1

1.	Unique identification code for product type:	n. TKLDD3Dfl-s1 LEGNI DEL DOGE multi-layer wood flooring
2.	Type, batch or serial number, or any other element with which to identify a construction product pursuant to article 11, paragraph 4:	Two-layer wood flooring • 1st layer: teak africa (4 / 5 mm) • 2nd layer: birch plywood (9 mm) Finishes code E - - - UV Varnish / Water-based varnish (transparent or with colored pigments) Finishes code P - - - unfinished Finishes code R - - - oiled finishes (transparent or with colored pigments)
3.	Intended use or uses of construction product, conforming to the relative harmonised technical specifications, as established by the manufacturer:	For use as internal flooring
4.	Manufacturer's name, registered trade name or mark And address, pursuant to article 11, paragraph 5:	ITLAS S.r.l. Società Benefit Via del lavoro 35 zona industriale 31016 Cordignano (TV)
6.	System or systems used to assess and verify the construction product's performance, as per appendix V:	System 4
9.	Declared performance:	

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONISED TECHNICAL SPECIFICATIONS
Reaction to fire	Dfl-s1	EN 14342:2013
Minimum average density	625 kg/m ³	
Minimum total thickness	12,5 mm	
End-use condition	Glue to substrate Without air gap underneath	
Formaldehyde emissions	E1	
Thermal Conductivity 1st layer teak africa	0,17 W/mK	
Thermal Conductivity 1st layer birch plywood	0,16 W/mK	
Thermal Resistance	0,0768 m ² K/W	
Slipperiness	NPD	
Breaking point	NPD	
Biological durability	Class 1-3	
PCP	≤ 5 ppm	

10. Performance of the product mentioned in points 1 and 2 hereof complies with the performance declared in point 9.

This Product Technical Statement is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer,
Cordignano, 15/01/2025

Cav. Patrizio Dei Tos
Itlas Srl Società Benefit Legal representative

