

DECLARATION OF PERFORMANCE n. WELDD3Cfl-s1

| | | |
|----|--|---|
| 1. | Unique identification code for product type: | n. WELDD3Cfl-s1 LEGNI DEL DOGE multi-layer wood flooring |
| 2. | Type, batch or serial number, or any other element with which to identify a construction product pursuant to article 11, paragraph 4: | Two-layer wood flooring • 1st layer: wengè (4 / 5 mm) • 2nd layer: birch plywood (9 mm) Finishes code A - - - UV Varnish (transparent or with colored pigments) Finishes code C - - -, H - - -, Y - - - water-based varnish (transparent or with colored pigments) Finishes code U - - - oil UV varnish (trasparent) |
| 3. | Intended use or uses of construction product, conforming to the relative harmonised technical specifications, as established by the manufacturer: | For use as internal flooring |
| 4. | Manufacturer's name, registered trade name or mark And address, pursuant to article 11, paragraph 5: | ITLAS S.r.l. Società Benefit Via del lavoro 35 zona industriale 31016 Cordignano (TV) |
| 6. | System or systems used to assess and verify the construction product's performance, as per appendix V: | System 3 |
| 7. | In the case of a declaration of performance concerning a construction product included in the application of harmonised standards : | Notified test laboratory (n°0497) CSI S.p.a. – 20030 Senago (MI) has carried out the tests regarding reaction to fire. Notified test laboratory (n°1937) Catas S.p.a. – 33048 S. Giovanni al Natisone (UD) has performed the tests regarding formaldehyde emissions. |

9. **Declared performance:**

| ESSENTIAL CHARACTERISTICS | PERFORMANCE | HARMONISED TECHNICAL SPECIFICATIONS |
|--|---|-------------------------------------|
| Reaction to fire | Cfl-s1 | EN 14342:2013 |
| Minimum average density | 640 kg/m ³ | |
| Minimum total thickness | 12,5 mm | |
| End-use condition | Glue to substrate Without air gap underneath | |
| Formaldehyde emissions | E1 | |
| Thermal Conductivity 1st layer wengè | 0,20 W/mK | |
| Thermal Conductivity 1st layer birch plywood | 0,16 W/mK | |
| Thermal Resistance | 0,05581 m ² K/W | |
| Slipperiness | NPD | |
| Breaking point | NPD | |
| Biological durability | Class 2 | |
| PCP | ≤ 5 ppm | |

10. **La prestazione del prodotto di cui ai punti 1 e 2 è conforme alla prestazione dichiarata di cui al punto 9.**

Si rilascia la presente dichiarazione di prestazione sotto la responsabilità esclusiva del fabbricante di cui al punto 4.

Firmato a nome e per conto del fabbricante,
Cordignano, 15/01/2025

Cav. Patrizio Dei Tos
Legale Rappresentante Itlas Srl Società Benefit

