ITLAS
IL LEGNO. LA TUA CASA.

Itlas - Società Benefit
Via del lavoro 35
31016 Cordignano
Treviso - Italy

t: +39 0438 368040
f: +39 0438 998331
e: info@itlas.it
www.itlas.com

DECLARATION OF PERFORMANCE n. NOTDP5Cfl-s1

1.	**Unique identification code for product type:**	**n. NOTDP5Cfl-s1** TAVOLE DEL PIAVE multi-layer wood flooring
2.	**Type, batch or serial number, or any other element with which to identify a construction product pursuant to article 11, paragraph 4:**	Three-layer wood flooring • 1st layer: european walnut (4 / 5 mm) • 2nd layer: birch playwood (6,5 mm) • 3rd layer: fir (5 mm) **Finishes code A - - -** UV Varnish (transparent or with colored pigments) **Finishes code C - - -**, **H - - -**, **Y - - -** water-based varnish (transparent or with colored pigments) **Finishes code U - - -** oil UV varnish (trasparent)
3.	**Intended use or uses of construction product, conforming to the relative harmonised technical specifications, as established by the manufacturer:**	For use as internal flooring
4.	**Manufacturer's name, registered trade name or mark And address, pursuant to article 11, paragraph 5:**	ITLAS S.r.l. Società Benefit Via del lavoro 35 zona industriale 31016 Cordignano (TV)
6.	**System or systems used to assess and verify the construction product's performance, as per appendix V:**	System 3
7.	**In the case of a declaration of performance concerning a construction product included in the application of harmonised standards :**	Notified test laboratory (n°0497) CSI S.p.a. – 20030 Senago (MI) has carried out the tests regarding reaction to fire. Notified test laboratory (n°1937) Catas S.p.a. – 33048 S. Giovanni al Natisone (UD) has performed the tests regarding formaldehyde emissions.

9. Declared performance:

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONISED TECHNICAL SPECIFICATIONS
Reaction to fire	Cfl-s1	EN 14342:2013
Minimum average density	540 kg/m3	
Minimum total thickness	15,5 mm	
End-use condition	Installation with or without air gap underneath	
Formaldehyde emissions	E1	
Thermal Conductivity 1st layer european walnut	0,16 W/mK	
Thermal Conductivity 1st layer birch playwood	0,16 W/mK	
Thermal Conductivity 1st layer fir	0,12 W/mK	
Thermal Resistance	0,10723 m2 K/W	
Slipperiness	NPD	
Breaking point	NPD	
Biological durability	Class 3	
PCP	≤ 5 ppm	

10. Performance of the product mentioned in points 1 and 2 hereof complies with the performance declared in point 9.

This Product Technical Statement is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer,
Cordignano, 15/01/2025

Cav. Patrizio Dei Tos
Itlas Srl Società Benefit Legal representative