ITLAS
IL LEGNO. LA TUA CASA.

Itlas - Società Benefit
Via del lavoro 35
31016 Cordignano
Treviso - Italy

t: +39 0438 368040
f: +39 0438 998331
e: info@itlas.it
www.itlas.com

# DECLARATION OF PERFORMANCE n. TKLDD3Cfl-s1

| | | |
|---|---|---|
| **1.** | **Unique identification code for product type:** | **n. TKLDD3Cfl-s1**<br>LEGNI DEL DOGE multi-layer wood flooring |
| **2.** | **Type, batch or serial number, or any other element with which to identify a construction product pursuant to article 11, paragraph 4:** | Two-layer wood flooring<br>• 1st layer: teak africa (4 / 5 mm)<br>• 2nd layer: birch playwood (9 mm)<br><br>**Finishes code A - - -**<br>UV Varnish (transparent or with colored pigments)<br>**Finishes code C - - -**, **H - - -**, **Y - - -**<br>water-based varnish (transparent or with colored pigments)<br>**Finishes code U - - -**<br>oil UV varnish (trasparent) |
| **3.** | **Intended use or uses of construction product, conforming to the relative harmonised technical specifications, as established by the manufacturer:** | For use as internal flooring |
| **4.** | **Manufacturer's name, registered trade name or mark And address, pursuant to article 11, paragraph 5:** | ITLAS S.r.l. Società Benefit<br>Via del lavoro 35 zona industriale<br>31016 Cordignano (TV) |
| **6.** | **System or systems used to assess and verify the construction product's performance, as per appendix V:** | System 3 |
| **7.** | **In the case of a declaration of performance concerning a construction product included in the application of harmonised standards :** | Notified test laboratory (n°0497) CSI S.p.a. – 20030 Senago (MI) has carried out the tests regarding reaction to fire.<br><br>Notified test laboratory (n°1937) Catas S.p.a. – 33048 S. Giovanni al Natisone (UD) has performed the tests regarding formaldehyde emissions. |

**9. Declared performance:**

| ESSENTIAL CHARACTERISTICS | PERFORMANCE | HARMONISED TECHNICAL SPECIFICATIONS |
|---|---|---|
| Reaction to fire | Cfl-s1 | EN 14342:2013 |
| Minimum average density | 625 kg/m3 | |
| Minimum total thickness | 12,5 mm | |
| End-use condition | Installation with or without air gap underneath | |
| Formaldehyde emissions | E1 | |
| Thermal Conductivity 1st layer teak africa | 0,17 W/mK | |
| Thermal Conductivity 1st layer birch playwood | 0,16 W/mK | |
| Thermal Resistance | 0,7683 m2 K/W | |
| Slipperiness | NPD | |
| Breaking point | NPD | |
| Biological durability | Class 1-3 | |
| PCP | ≤ 5 ppm | |

**10. Performance of the product mentioned in points 1 and 2 hereof complies with the performance declared in point 9.**

This Product Technical Statement is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer,
**Cordignano, 15/01/2025**

**Cav. Patrizio Dei Tos**
Itlas Srl Società Benefit Legal representative